

## TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

### CLASSIFICATION

	Norm	Tarkett value
Flooring Type	ISO 2424	Carpet Modular
Product type	EN 1307	Textile floor coverings (EN 1307)
Commercial classification	ISO 10874	33 Heavy

### TECHNICAL CHARACTERISTICS

	Norm	Tarkett value
Items per box	-	20
Manufacture type	ISO 2424	Tuft
Pile construction	-	Structured pile
Secondary backing	ISO 2424	B1 ProBase
Total thickness	ISO 1765	6 mm
Effective pile thickness	ISO 1766	3,10 mm
Total weight	ISO 8543	4100 g/m²
Total pile mass	ISO 2424	590 g/m²
Effective pile mass	ISO 8543	405 g/m²
Pile density	ISO 8543	0 g/cm³
Number of Knots (no./m²)	ISO 1763	1580
Product Material	-	Tufted

### PERFORMANCE FOR CE MARKING

	Norm	Tarkett value
Declaration of Performance #	EN 14041	0493-CPR-0002-02
Reaction to fire	EN 13501-1	Bfl-s1
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)
Thermal resistance (m²-K/W)	ISO 8302	,0.0590

### TECHNICAL PERFORMANCE

	Norm	Tarkett value
Impact sound reduction - ΔLw	ISO 10140	24 dB
Sound absorption - αw	ISO 354	0,15
Luxury rating	EN 1307	LC2
Castor chair effect	ISO 4918	Intensive use
Underfloor heating	-	Suitable
Colour fastness to light	ISO 105-B02	≥ 5
Colour fastness to water - Staining	ISO 105-E01	≥ 2-3
Colour fastness to water - Colour change	ISO 105-E01	≥ 3-4
Colour fastness to rubbing - Wet cloth	ISO 105-X12	≥ 3
Colour fastness to rubbing - Dry cloth	ISO 105-X12	≥ 3

### SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Norm	Tarkett value
Material Health Statement	-	Available
Global Green Tag	-	Level A
Cradle to Cradle®	-	Silver
Phthalate content	-	100% Phthalate-free
Tarkett Indoor Air Quality (TVOC after 28 days)	EN 16516	Gold ( $\leq 100 \mu\text{g} / \text{m}^3$ )
EPD available	-	Yes