

TECHNICAL AND ENVIRONMENTAL SPECIFICATIONS

CLASSIFICATION

	Norm	Tarkett value
Flooring Type	ISO 2424	Carpet Modular
Product type	EN 1307	Textile floor coverings (EN 1307)
Commercial classification	ISO 10874	33 Heavy

TECHNICAL CHARACTERISTICS

	Norm	Tarkett value
Items per box	-	20
Manufacture type	ISO 2424	Tuft
Pile construction	-	Loop pile
Secondary backing	ISO 2424	B1 ProBase
Total thickness	ISO 1765	7 mm
Effective pile thickness	ISO 1766	3,90 mm
Total weight	ISO 8543	4100 g/m²
Total pile mass	ISO 2424	680 g/m²
Effective pile mass	ISO 8543	435 g/m²
Pile density	ISO 8543	0 g/cm³
Number of Knots (no./m²)	ISO 1763	1540
Product Material	-	Tufted

PERFORMANCE FOR CE MARKING

	Norm	Tarkett value
Declaration of Performance #	EN 14041	0493-CPR-0002-02
Reaction to fire	EN 13501-1	Bfl-s1
Slip resistance	EN 13893	Class DS ($\mu \geq 0,30$)
Thermal resistance (m²-K/W)	ISO 8302	,0.0870

TECHNICAL PERFORMANCE

	Norm	Tarkett value
Impact sound reduction - ΔL_w	ISO 10140	28 dB
Sound absorption - α_w	ISO 354	0,15
Luxury rating	EN 1307	LC2
Castor chair effect	ISO 4918	Intensive use
Underfloor heating	-	Suitable
Colour fastness to light	ISO 105-B02	≥ 5
Colour fastness to water - Staining	ISO 105-E01	$\geq 2-3$
Colour fastness to water - Colour change	ISO 105-E01	$\geq 3-4$
Colour fastness to rubbing - Wet cloth	ISO 105-X12	≥ 3
Colour fastness to rubbing - Dry cloth	ISO 105-X12	≥ 3

SUSTAINABILITY, ENVIRONMENT & INDOOR AIR QUALITY

	Norm	Tarkett value
Global Green Tag	-	Level A
Cradle to Cradle®	-	Bronze
Phthalate content	-	100% Phthalate-free
Tarkett Indoor Air Quality (TVOC after 28 days)	EN 16516	≤ 1000 µg / m³